



San Diego Unified
SCHOOL DISTRICT

Linda Hippe, CPPB
Senior Contracts Specialist
Strategic Sourcing and Contracts Department
P - 858-522-5831
F - 858-522-5885
lhippe@sandi.net

August 6, 2015

NO. CZ-16-0043-29 – DESIGN, FURNISH AND INSTALL SYNTHETIC TURF FIELD AND TRACKS ON AN AS-NEEDED BASIS (IDIQ)

DEADLINE DATE: AUGUST 11, 2015 AT 1:00 P.M.*

ADDENDUM TO BID NO. 3

Please note the following revisions for the above referenced bid:

Changes made by the District:

1. Revisions to Part 4: Technical Specification Section G20 Site Improvements. See changes on pages 11, 25 and 26 included in this addendum.

Changes made by the AOR:

1. None.

Revisions have been **bolded**, *italicized*, or struck through. Please include this addendum in your original bid documents and acknowledge receipt accordingly on the Bid Proposal Form. If you have questions regarding this bid or the revisions, please contact me at (858) 522-5831.

Sincerely,

Linda Hippe, CPPB
Senior Contract Specialist

c: Loren Chico

Guide and the Track and Field and Cross Country Rule Book. Maximum variation in surface shall be 1/8 inch in 10 feet.

G204007 1.1.3 - Track Surface

Provide ~~CalTrax-IMS™ manufactured by California Track & Engineering, Inc.,~~ **BSS 100, manufactured by Beynon, A Tarkett Sports Company**, or equal. Color of wearing surface shall be manufacturer' standard color red.

G204007 1.1.4 - Track Markings

Provide track markings using polyurethane paint compatible with the track surfacing. Provide lane lines, starting lines, finish lines, etc., for California Interscholastic Federation Southern Section (CIFSS) standard track events as directed by the Project Manager. Markings shall comply with requirements the diagram titled "400 Meter Event Markings Layout" per NFHS Court and Field Diagram Guide. In addition, markings shall include the school name and team nickname, i.e., "San Diego Cavers."

G204007 1.1.5 - Track Curbs

Provide reinforced concrete curb at outer perimeter of track, minimum 6 inch wide by 18 inch deep. Curb shall include 2 inch wide by ½ deep notch on the top surface to receive track surfacing.

G204007 1.1.6 - Warranty

Provide track surface manufacturer's five (5) year warranty against faulty workmanship and material failure.

G204007 1.2 - STANDARD RUNNING TRACK – TYPE II

Running track shall be a standard 400 meter configuration track with start and finish chutes as shown in the diagram titled "Runways Inside Curve" for equal quadrant track, per the NFHS Court and Field Diagram Guide, except that the track shall include 9 lanes. Locate chutes on the home side of the track.

G204007 1.2.1 - Track Subbase

Provide compacted subbase as required by the track surfacing material manufacturer and as recommended in the geotechnical report. Under no circumstances use recycled materials for track subbase.

G204007 1.2.2 - Track Base

Provide porous asphalt track base. Thickness shall be as required by the track surfacing material manufacturer and as recommended in the geotechnical report. Maximum slope and cross slope shall be as required by the NFHS Court and Field Diagram Guide and the Track and Field and Cross Country Rule Book. Maximum variation in surface shall be 1/8 inch in 10 feet.

G204007 1.2.3 - Track Surface

Provide porous track surface, ~~CalTrax-MS™ manufactured by California Track & Engineering, Inc.,~~ **BSS 100, manufactured by Beynon, A Tarkett Sports Company**, or equal. Color of wearing surface shall be manufacturer' standard color red.

G204007 1.2.4 - Track Markings

G204007 1.11.2 - Track Base

Provide asphalt track base. Thickness shall be as required by the track surfacing material manufacturer and as recommended in the geotechnical report, but shall be no less than 3 inches. Maximum slope in the running direction shall be limited to 1 percent and maximum cross slope shall be limited to 2 percent. Maximum variation in surface shall be 1/8 inch in 10 feet.

G204007 1.11.3 - Track Surface

Provide ~~CalTrax-IMS™ manufactured by California Track & Engineering, Inc.,~~ **BSS 100, manufactured by Beynon, A Tarkett Sports Company**, or equal. Color of wearing surface shall be manufacturer' standard color red.

G204007 1.11.4 - Track Markings

Provide track markings using polyurethane paint compatible with the track surfacing. Provide lane lines, starting lines, finish lines, etc., for California Interscholastic Federation Southern Section (CIFSS) standard track events as directed by the Project Manager. Markings shall comply with requirements the diagram titled "400 Meter Event Markings Layout" per NFHS Court and Field Diagram Guide except locations of all markings shall be adjusted to the size of the track. In addition, markings shall include the school name and team nickname, i.e., "Vista Grande Koalas."

G204007 1.11.5 - Track Curbs

Provide reinforced concrete curb at outer perimeter of track, minimum 6 inch wide by 18 inch deep. Curb shall include 2 inch wide by ½ deep notch on the top surface to receive track surfacing.

G204007 1.11.6 - Warranty

Provide track surface manufacturer's five (5) year warranty against faulty workmanship and material failure.

G204007 1.12 - NON-STANDARD RUNNING TRACK – TYPE II

Running track shall be a standard 400 meter configuration track with start and finish chutes as shown in the diagram titled "Runways Inside Curve" for equal quadrant track, per the NFHS Court and Field Diagram Guide, except that all dimensions other than lane width shall be 1/2 of those shown on the diagram, and except that the track shall include 6 lanes.

G204007 1.12.1 - Track Subbase

Provide compacted subbase as required by the track surfacing material manufacturer and as recommended in the geotechnical report. Under no circumstances use recycled materials for track subbase.

G204007 1.12.2 - Track Base

Provide asphalt track base. Thickness shall be as required by the track surfacing material manufacturer and as recommended in the geotechnical report, but shall be no less than 3 inches. Maximum slope in the running direction shall be limited to 1 percent and maximum cross slope shall be limited to 2 percent. Maximum variation in surface shall be 1/8 inch in 10 feet.

G204007 1.12.3 - Track Surface

Provide CalTrax IMS™ ~~manufactured by California Track & Engineering, Inc., BSS 100, manufactured by Beynon, A Tarkett Sports Company~~, or equal. Color of wearing surface shall be manufacturer' standard color red.

G204007 1.12.4 - Track Markings

Provide track markings using polyurethane paint compatible with the track surfacing. Provide lane lines, starting lines, finish lines, etc., for California Interscholastic Federation Southern Section (CIFSS) standard track events as directed by the Project Manager. Markings shall comply with requirements the diagram titled "400 Meter Event Markings Layout" per NFHS Court and Field Diagram Guide except locations of all markings shall be adjusted to the size of the track. In addition, markings shall include the school name and team nickname, i.e., "Vista Grande Koalas."

G204007 1.12.5 - Track Curbs

Provide reinforced concrete curb at outer perimeter of track, minimum 6 inch wide by 18 inch deep. Curb shall include 2 inch wide by ½ deep notch on the top surface to receive track surfacing.

G204007 1.12.6 - Warranty

Provide track surface manufacturer's five (5) year warranty against faulty workmanship and material failure.

G204007 1.13 - SYNTHETIC TURF PLAYFIELD

Provide synthetic turf playfield for elementary or middle school use. Playfield area shall be 40,000 sq. ft.

When directed by the Project Manager and as a Unit Price item, provide playfield of area greater than that stated above.

G204007 1.13.1 - Subbase

Provide compacted subbase as required by the synthetic turf manufacturer and as recommended by the geotechnical report.

G204007 1.13.2 - Field Drainage System

Provide field drainage system per Section G204007, Para. 1.3.2, herein.

G204007 1.13.3 - Field Irrigation System

Provide field irrigation system per Section G204007, Para. 1.4.3, herein.

G204007 1.13.5 - Synthetic Turf

Provide FieldTurf® Synthetic Grass System, manufactured and installed by FieldTurf Tarkett. Provide FieldTurf® Classic HD, color green. Provide FieldTurf® CoolPlay infill consisting of layered cork dressing, cryogenic rubber/silica sand mix, and silica sand. This is a required product and no substitution will be allowed.

G204007 1.13.6 - Curb

Provide flush reinforced concrete curb at outer perimeter of field, minimum 6 inch wide by 12 inch deep. Curb shall include turf manufacturer's standard wood molding for attachment of turf.